

TRACKLIGHT LED 3.1



Advantages

- Ability to direct the light beam as desired
- Quick and easy installation
- Branded components
- Solid aluminum housing
- High CRI>90

IP20



TRACKLIGHT LED 3.1



P



Ra

IP



	P	lm	K	Ra	IP		kg
TRC3ST.11.013.8D2700	13	1700	2700K	>80	IP20	20°X20° 35°X35° 50°X50° 65°X65° 15°X15°	0,7kg
TRC3ST.11.013.8D3000	13	1700	3000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.8D4000	13	1750	4000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.8D5000	13	1750	5000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.8E2000	13	1100	2000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.8E2500	13	1500	2500K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9D2700	13	1500	2700K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9D3000	13	1500	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9D4000	13	1550	4000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg

TRC3ST.11.013.9E3000	13	1400	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9E4200	13	1250	4200K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9E5700	13	1600	5700K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9F3000	13	1400	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9G3000	13	1600	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9G3500	13	1650	3500K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.11.013.9G4000	13	1700	4000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg

TRACKLIGHT LED 3.1 2

	P			Ra	IP		
TRC3ST.21.019.8D2700	19	2400	2700K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.8D3000	19	2400	3000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.8D4000	19	2500	4000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.8D5000	19	2500	5000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.8E2000	19	1550	2000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.8E2500	19	2100	2500K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9D2700	19	2150	2700K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9D3000	19	2150	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9D4000	19	2250	4000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg

TRC3ST.21.019.9E3000	19	1950	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9E4200	19	1750	4200K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9E5700	19	2250	5700K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9F3000	19	2000	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9G3000	19	2250	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9G3500	19	2300	3500K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.21.019.9G4000	19	2400	4000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg

TRACKLIGHT LED 3.1 3


	P			Ra	IP		
TRC3ST.31.021.8D2700	21	2650	2700K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.8D3000	21	2650	3000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.8D4000	21	2750	4000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.8D5000	21	2750	5000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.8E2000	21	1650	2000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.8E2500	21	2300	2500K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9D2700	21	2400	2700K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9D3000	21	2400	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9D4000	21	2500	4000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg

TRC3ST.31.021.9E3000	21	2150	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9E4200	21	1950	4200K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9E5700	21	2500	5700K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9F3000	21	2200	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9G3000	21	2400	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9G3500	21	2450	3500K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.31.021.9G4000	21	2600	4000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg

TRACKLIGHT LED 3.1 4

	P			Ra	IP		
TRC3ST.41.023.8D2700	23	2900	2700K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.8D3000	23	2900	3000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.8D4000	23	3000	4000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.8D5000	23	3000	5000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.8E2000	23	1800	2000K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.8E2500	23	2500	2500K	>80	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9D2700	23	2600	2700K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9D3000	23	2600	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9D4000	23	2700	4000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg

TRC3ST.41.023.9E3000	23	2300	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9E4200	23	2100	4200K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9E5700	23	2700	5700K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9F3000	23	2050	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9G3000	23	2350	3000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9G3500	23	2400	3500K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg
TRC3ST.41.023.9G4000	23	2550	4000K	>90	IP20	15°X15° 20°X20° 35°X35° 50°X50° 65°X65°	0,7kg




	H	W	L
TRC3ST.1	96	0	84
TRC3ST.2	96	0	84
TRC3ST.3	96	0	84
TRC3ST.4	96	0	84


Montage




3-phase rail




Luminous flux




15°X15°




20°X20°



35°X35°



50°X50°



65°X65°

Available configurations

Family	Power version	Version	Power [W]	CRI	Type of diode	CCT [K]	Lens material	Diffuser material	Beam angle	Control	Operating temperature	Warranty	Modifications
TRC3ST TRACKLIGHT T LED 3.1	1 1	1 Lift 1	013 13W	8 >80	D COB	2000 2000K	0 No lens	S35 ABS reflector Glossy	015015 15°x15°	00 On/Off	2035 -20°C÷35°C	05Y 5 Years	B001 Black, RAL9005
	2 2		019 19W	9 >90	E COB Food/Special App	2500 2500K			020020 20°x20°				W001 White, RAL9016
	3 3		021 21W		F COB Premium White	2700 2700K			035035 35°x35°				
	4 4		023 23W		G COB Premium White	3000 3000K			050050 50°x50°				
						3500 3500K			065065 65°x65°				
						4000 4000K							
						4200 4200K							
						5000 5000K							
						5700 5700K							

Example product code

TRC3ST.11.013.8D3000.0S35.015015.00.2035.05Y.W001